



群韻科技企業股份有限公司 (C&C TEK CORP.)

10F., No.236-1, Jhongsing Rd.,
Sijhih City, Taipei County 221, Taiwan
TEL: 886-2-2695-8710 FAX: 886-2-2695-8712
[Http://www.cccoil.com.tw](http://www.cccoil.com.tw)
e-mail : grace@cccoil.com.tw

| PART NUMBER | Impedance () At 100MHz | DC Resistance () MAX. | Rated Current (mA) MAX. |
|-----------------|----------------------------|---------------------------|----------------------------|
| CMB 160808Z-600 | 60±25% | 0.2 | 300 |
| CMB 160808Z-800 | 80±25% | 0.2 | 300 |
| CMB 160808Z-121 | 120±25% | 0.2 | 200 |
| CMB 160808Z-221 | 220±25% | 0.2 | 200 |
| CMB 160808Z-301 | 300±25% | 0.35 | 200 |
| CMB 160808Z-451 | 450±25% | 0.4 | 250 |
| CMB 160808Z-601 | 600±25% | 0.45 | 200 |
| CMB 160808Z-102 | 1000±25% | 0.6 | 100 |
| CMB 160808U-600 | 60±25% | 0.2 | 300 |
| CMB 160808U-800 | 80±25% | 0.2 | 300 |
| CMB 160808U-121 | 120±25% | 0.2 | 200 |
| CMB 160808U-221 | 220±25% | 0.2 | 200 |
| CMB 160808U-301 | 300±25% | 0.35 | 200 |
| CMB 160808U-451 | 450±25% | 0.4 | 200 |
| CMB 160808U-601 | 600±25% | 0.45 | 200 |
| CMB 160808U-102 | 1000±25% | 0.6 | 100 |
| CMB 160808G-600 | 60±25% | 0.2 | 300 |
| CMB 160808G-800 | 80±25% | 0.2 | 300 |
| CMB 160808G-121 | 120±25% | 0.2 | 200 |
| CMB 160808G-221 | 220±25% | 0.2 | 200 |
| CMB 160808G-301 | 300±25% | 0.35 | 200 |
| CMB 160808G-451 | 450±25% | 0.4 | 200 |
| CMB 160808G-601 | 600±25% | 0.45 | 200 |
| CMB 160808G-102 | 1000±25% | 0.6 | 100 |
| CMB 160808G-152 | 1500±25% | 0.7 | 50 |
| CMB 160808G-202 | 2000±25% | 0.8 | 50 |
| CMB 160808B-400 | 40±25% | 0.3 | 300 |
| CMB 160808B-600 | 60±25% | 0.3 | 300 |
| CMB 160808B-800 | 80±25% | 0.3 | 200 |
| CMB 160808B-121 | 120±25% | 0.3 | 200 |
| CMB 160808B-181 | 180±25% | 0.35 | 200 |
| CMB 160808B-221 | 220±25% | 0.4 | 200 |
| CMB 160808B-301 | 300±25% | 0.45 | 200 |
| CMB 160808B-601 | 600±25% | 0.65 | 200 |
| CMB 160808B-102 | 1000±25% | 0.8 | 50 |
| CMB 160808L-150 | 15±25% | 0.3 | 200 |

| | | | |
|-----------------|---------|------|-----|
| CMB 160808L-300 | 30±25% | 0.3 | 200 |
| CMB 160808L-600 | 60±25% | 0.3 | 200 |
| CMB 160808L-800 | 80±25% | 0.4 | 150 |
| CMB 160808L-121 | 120±25% | 0.4 | 150 |
| CMB 160808L-221 | 220±25% | 0.45 | 150 |
| CMB 160808L-301 | 300±25% | 0.6 | 100 |